

JZ-HF

No.cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
2 x 0,5	5,0	9,6	38,0	20
3 G 0,5	5,3	14,0	44,0	20
4 G 0,5	5,7	19,0	52,0	20
5 G 0,5	6,4	24,0	67,0	20
7 G 0,5	7,6	34,0	91,0	20
7 x 0,5	7,6	34,0	91,0	20
10 G 0,5	9,3	48,0	128,0	20
12 G 0,5	9,3	58,0	137,0	20
14 G 0,5	9,8	67,0	158,0	20
16 G 0,5	10,3	77,0	182,0	20
18 G 0,5	11,2	86,0	207,0	20
20 G 0,5	11,6	96,0	226,0	20
25 G 0,5	13,6	120,0	292,0	20
30 G 0,5	13,7	144,0	330,0	20
34 G 0,5	15,0	163,0	387,0	20
36 G 0,5	15,0	173,0	399,0	20
42 G 0,5	16,3	202,0	449,0	20
50 G 0,5	17,8	240,0	573,0	20
61 G 0,5	19,3	290,0	682,0	20
2 x 0,75	5,5	14,0	44,0	19
3 G 0,75	5,7	22,0	53,0	19
4 G 0,75	6,4	29,0	67,0	19
5 G 0,75	7,0	36,0	81,0	19
7 G 0,75	8,4	50,0	111,0	19
10 G 0,75	10,3	72,0	159,0	19
12 G 0,75	10,3	86,0	174,0	19
12 x 0,75	10,3	86,0	174,0	19
14 G 0,75	10,9	101,0	201,0	19
14 x 0,75	10,9	101,0	201,0	19
16 G 0,75	11,5	115,0	225,0	19
18 G 0,75	12,2	130,0	249,0	19
20 G 0,75	12,9	144,0	282,0	19
25 G 0,75	14,5	180,0	375,0	19

JZ-HF

No.cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
30 G 0,75	15,2	216,0	411,0	19
34 G 0,75	16,6	245,0	473,0	19
36 G 0,75	16,6	259,0	509,0	19
42 G 0,75	18,3	302,0	602,0	19
50 G 0,75	20,0	360,0	706,0	19
61 G 0,75	21,3	432,0	886,0	19
65 G 0,75	22,0	439,0	899,0	19
2 x 1	5,7	19,0	62,0	18
3 G 1	6,0	29,0	64,0	18
4 G 1	6,8	38,0	80,0	18
5 G 1	7,5	48,0	97,0	18
7 G 1	8,9	67,0	132,0	18
10 G 1	10,9	96,0	187,0	18
12 G 1	10,9	115,0	206,0	18
14 G 1	11,6	134,0	239,0	18
16 G 1	12,3	154,0	274,0	18
18 G 1	13,0	173,0	307,0	18
20 G 1	13,7	192,0	336,0	18
25 G 1	15,6	240,0	443,0	18
30 G 1	16,4	288,0	558,0	18
34 G 1	17,8	326,0	601,0	18
36 G 1	17,8	346,0	623,0	18
41 G 1	19,4	403,0	710,0	18
42 G 1	19,4	403,0	730,0	18
50 G 1	21,1	480,0	868,0	18
61 G 1	22,8	586,0	1044,0	18
65 G 1	23,6	624,0	1195,0	18
2 x 1,5	6,5	29,0	69,0	16
3 G 1,5	6,9	43,0	84,0	16
4 G 1,5	7,5	58,0	103,0	16
5 G 1,5	8,4	72,0	129,0	16
7 G 1,5	10,1	101,0	177,0	16
8 G 1,5	11,1	115,0	206,0	16
10 G 1,5	11,9	144,0	248,0	16

JZ-HF

No.cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
12 G 1,5	12,3	173,0	283,0	16
14 G 1,5	13,1	202,0	327,0	16
16 G 1,5	14,0	230,0	372,0	16
18 G 1,5	14,7	259,0	418,0	16
20 G 1,5	15,7	288,0	469,0	16
25 G 1,5	17,5	360,0	631,0	16
30 G 1,5	18,7	432,0	701,0	16
34 G 1,5	20,3	490,0	800,0	16
36 G 1,5	20,3	518,0	831,0	16
42 G 1,5	22,1	605,0	987,0	16
50 G 1,5	24,0	720,0	1241,0	16
60 G 1,5	25,4	864,0	1431,0	16
61 G 1,5	25,9	878,0	1495,0	16
65 G 1,5	26,8	936,0	1566,0	16
2 x 2,5	8,1	48,0	102,2	14
3 G 2,5	8,6	72,0	129,0	14
4 G 2,5	9,6	96,0	160,0	14
5 G 2,5	10,5	120,0	201,0	14
7 G 2,5	12,9	168,0	278,0	14
10 G 2,5	15,3	240,0	398,0	14
12 G 2,5	15,3	288,0	444,0	14
14 G 2,5	16,8	336,0	512,0	14
16 G 2,5	17,7	384,0	615,0	14
18 G 2,5	18,8	432,0	678,0	14
20 G 2,5	20,0	480,0	752,0	14
25 G 2,5	22,5	600,0	1060,0	14
30 G 2,5	24,0	720,0	1197,0	14
34 G 2,5	26,0	816,0	1337,0	14
36 G 2,5	26,0	864,0	1384,0	14
42 G 2,5	28,5	1008,0	1599,0	14
50 G 2,5	30,6	1200,0	1854,0	14
3 G 4	10,5	115,0	213,0	12
4 G 4	11,5	154,0	265,0	12
5 G 4	12,8	192,0	328,0	12
4 G 6	13,3	230,0	382,0	10

JZ-HF

No. cores x cross-sec. mm ²	Outer Ø app. mm	Cop. weight kg / km	Weight app. kg / km	AWG-No.
5 G 6	14,6	288,0	461,0	10
4 G 10	17,8	384,0	652,0	8
5 G 10	19,7	480,0	790,0	8
4 G 16	20,8	614,0	1007,0	6
5 G 16	23,3	768,0	1304,0	6